

Microphone Cables

Microphone Stereo Cable (Stranded Conductor, High Constructive Cable)

Jacket Color
Cable Construction
<p>Packing Information</p> <p>Length : 100M/Coil : 300M/Coil : 500M/Coil</p>

Applications

- Studio Broadcasting
- Music Hall
- Professional Show Occasions
- Home Theater

Our Microphone Stereo Cable utilizes the Fined Stranded Tinned Copper Conductor in order to provide high quality sound/frequency respond to the audio signal. The Polyethylene, PE, of which insulation is made, strengthens insulation and lowers capacitance. No oxidation and UV protection due to the use of Tinned Copper Wire Braid. The 100% overlapped Al/P-Foil and high density tinned copper wire braiding clears up EMI, and effectively prevents noises from mechanical vibration and twist. The cable has strong flexible property. Soft, highly flexible PVC jacket has durability and elegant matte finish. Also provided is high quality non-migration PVC.

Physical Construction / Properties

Product Code	CM-M2-2525
Inner Conductor	16/0.10 BC
Conductor Cross Section	2x0.210 SQ.mm.
Insulation	1.20mm. PE
Filler	Cotton
No. of Pair	1
Core Arrangements	2 Core Twisted with shield
1 st Shield	0.10x58 BC
Outer Jacket	5.50mm PVC (Soft-Flex)
Voltage Rating	300 V
Temperature Rating	80 C