

Microphone Mono Cable

(Stranded Conductor, High Constructive cable)

Microphone Cables

Applications

- Studio Broadcasting
- Music Hall
- Professional Show Occasions
- Home Theater

Our Microphone Mono Cable utilizes the Finned Stranded Tinned Copper Conductor in order to provide high quality sound/frequency respond to the audio signal. The Polyethylene, PE, of which insulation is made, strengthens insulation and lowers capacitance. No oxidation and UV protection due to the use of Tinned Copper Wire Braid. The 100% overlapped Al/P-Foil and high density tinned copper wire braiding clears up EMI, and effectively prevents noises from mechanical vibration and twist. The cable has strong flexible property. Soft, highly flexible PVC jacket has durability and elegant matte finish. Also provided is high quality non-migration PVC.

Jacket Color ■	
Cable Construction	
Packing Information Length : 100M/Coil : 300M/Coil : 500M/Coil Others please specified	

Physical Construction/Properties	
Product Code	CM-M1-2424
Inner Conductor	13/Ø 0.14 mm Finned Stranded inned Copper
Conductor Cross Section	1 x 0.202 Sq.mm (24AWG)
Insulation	Ø 2.70 mm PE
Core Arrangement	1 Core
1 st Shield	AL/P-Foil
2 nd Shield	Ø 0.10x8x16 Tinned Copper Clad Aluminum Braid (90% Coverage)
Outer Jacket	Ø 5.90 mm PVC (Soft-Flex), Black
Voltage Rating	300V
Temperature Rating	80C