

Multicore Snake Cable

High density shielding cable specially designed and manufactured under the USA and Japanese Standard

Applications

- Studio Broadcasting
- Music Hall
- Professional Show Occasions
- Home Theater

Our Microphone Stereo Cable utilizes the Finned Stranded Tinned Copper Conductor in order to provide high quality sound / frequency respond to the audio signal. The Polyethylene, PE, of which insulation is made, strengthens insulation and lowers capacitance. No oxidation and UV protection due to the use of Tinned Copper Wire Braid. The 100% overlapped AL/P-Foil and high density tinned copper wire braiding clears up EMI, and effectively prevents noises from mechanical vibration and twist. The cable has strong flexible property. Soft, highly flexible PVC jacket has durability and elegant matte finish. Also provided is high quality non-migration PVC.

Jacket Color	■
Cable Construction	
<p>Packing Information</p> <p>Lenght : 100M/Coil : 500M/Coil</p>	

Physical Construction/Properties							
Product Code	CM-MS-9902	CM-MS-9904	CM-MS-9908	CM-MS-9912	CM-MS-9916	CM-MS-9924	CM-MS-9932
Inner Conductor	30/0.10mm BC						
Conductor Cross Section	2x1.10 SQ.mm.						
Insulation	3.00 mm.						
Filter	Cotton						
No. of Pair	2	4	8	12	16	24	32
Core Arrangements	2 Core Twisted with shield						
1st Shield	0.2x7 TC						
2nd Shield	AL/P-Foil						
Outer Jacket	8.00mm. PVC (Soft-flex), Black	10.00mm. PVC (Soft-flex), Black	13.00mm. PVC (Soft-flex), Black	15.00mm. PVC (Soft-flex), Black	17.00mm. PVC (Soft-flex), Black	21.00mm. PVC (Soft-flex), Black	25.00mm. PVC (Soft-flex), Black
Voltage Rating	300 V.						
Temperature Rating	80 C						