



Outdoor Drop Wire Speaker Cable

(Outdoor Speaker Cable With Messenger)

Outdoor Drop Wire Cable

Jacket Color ■

Outdoor Drop Wire Cable

Packing Information

Length : 200M/Coil
 : 500M/Coil
 : 1000M/Spool

Applications

- Interconnecting Outdoor PA/Sound System
- Interconnecting Village Audio Broadcasting System
- Stranded or Solid, Copper or Copper Clad Steel Center Conductor
- High Strength Galvanized Steel Support Wire
- High Quality PVC Jacket
- Stranded or Solid, Copper or Copper Clad Steel Center Conductor
- High Strength Galvanized Steel Support Wire
- High Quality PVC Jacket

Physical Construction

Product Code	No. of Core	Conductor Diameter (mm)	Nominal Insulation Thickness (±20mm)	Nominal Diameter of Support (mm)	Approx. Overall Diameter	
					A (±20mm)	B (±20mm)
CM-SM-1716	2	30/0.25 BC (1.50)	0.5	1.2	7.3	8
CM-SM-1714	2	30/0.30 BC (2.10)	0.5	1.2		

Electrical Specifications

@ 20 C	0.93 mm Bare Copper	1.50 mm Bare Copper	2.10 mm Bare Copper
Nom. Inner DC Resistance	19.27 Ohm/Km	14.38 Ohm/Km	9.31 Ohm/Km
Rate Volt	300 V	300 V	300 V
Rate Temperature	80 C	80 C	80 C

Note : BC = Bare Copper